



EASY

GYS 3106LB SG63



Product Features and Key Data

Applications :	Commercial building, parking, hospitals, etc...
Luminaire Type :	LED Exit light
Mounting Method :	Surface or Pendant
Luminaire Optic :	Clear Glass
Connected Load :	6W
Colour Temprature :	6000K
Rated Luminous Flux :	480 lm
Luminous Efficiency :	80 lm/W
Power Factor :	> 0,930
CRI Value :	> 80
UGR :	< 21 (ENI24664-1)
Photo Biological Class :	Group 0 - No risk
Luminaire Colour :	White color
Luminaire Body :	Aluminium body with glass.
Electrical version :	With electronic transformer, switchable.
Connection method :	Terminal
Mains frequency :	50/60 Hz
Mains voltage :	220 - 240 V
Led Service (25°) :	L80 = 50.000 h
Driver (220 - 240V) :	Gecem
Ceiling Type :	AB - Gypsum Ceiling TB - Modular Ceiling KB - Clip-in Ceiling
Ingress Protection (IP) rating :	IP20
Protection class :	I
Impact resistance (IK) :	IK02
Hot wire resistance :	650 °C
Ambient temperature :	- 20 - 35 °C
Options :	1 - 3 Hours Emergency Kit (standard 3 hours emergency kit)
Accessories :	Stickers (arrows direction can be change)